▶ 15" LCD DISPLAY

X-15AV/X-15A

▶ FEATURES

- Distinctive aluminum alloy housing for added strength
- Fast 16ms response time
- NeoV Optical Filter™
- Swift 16ms response time
- High 500 brightness
- DVI ready for high quality signal
- S-Video* and CVBS* inputs
- Auto-adjustment for optimal setting
- Kensington® security slot

▶ SPECIFICATION

Panel	**Panel Type**	TFT LCD
	Panel Size	15.0" (381mm)
	Max. Resolution	XGA 1024 x 768
	Pixel Pitch	0.297mm
	Brightness	500cd/m^2 (Typical)
	Contrast Ratio	400:1 (Typical)
	Surface Treatments	Hard Coating (3H), Anti-glare Treatment
	Viewing Angle (H/V)	140°/130° (Typical)
	Display Color	16.7M
	Response Time	16ms
	Frequency (H/V)	H: 30kHz - 60kHz V: 50Hz - 75Hz
	Max. Pixel Clock	80MHz
	Life Time	30,000hrs (Minimum)
Input	**Analog**	15-Pin D-Sub
	Digital	29-Pin DVI-D
	S-Video*	4-Pin Mini Din S-Video
	CVBS*	CVBS Jack
Connector	**Power**	3-Pin AC Plug
NeoV Optical Filter	**Thickness**	3.0mm (0.18")
	Reflection Rate	<1%
	Transmission Rate	>96%
	Hardness	>6H (MOH's Rating)
Tilt	**Tilt**	0° ~ +20°
Mounting	**VESA FPMPMI**	Yes (100mm)
Regulation Approval	**Safety & EMI**	FCC, UL/CUL, CE, TUV/BAURT, TCO 95, BSMI, ISO 13406-2, EPA, CB
	VESA	DDC 1/2B, DPMS
Power	**Power AC Consumption**	100 - 240V, 50 - 60Hz <48W (On) <4W (Stand-by) <2W (Off)
Dimensions	**Net (W x H x D)**	380 x 359 x 155mm (15.0" x 14.1" x 6.1")
	Packing (W x H x D)	445 x 490 x 225mm (17.5" x 19.2" x 8.9")
Weight	**Net Weight**	4.8Kg (10.6lbs)
	Gross Weight	7.0Kg (15.4lbs)
Packing	**1 Pallet**	40 Cartons
	20' Container	480 Sets
	40' Container	1040 Sets

*Video function is only available on X-15AV

All specifications are subject to change without prior notice.

www.agneovo.com

Copyright © 2005 AG Neovo. All rights reserved.
The name AG Neovo is a trademark of Associated Industries China, Inc.
All other trademarks are the property of their respective owners.

Version 5.0, 04/11/2005